



Application

The G5 series aluminum garage fixture is an ideal choice for replacement of common High Pressure Sodium and Metal Halide Garage fixtures. Its electronic ballast features a high >0.98 power factor for cool, efficient, flicker-free operation. Common applications include: service hallways, parking garages, loading docks, stairwells, utility closets, gas stations, shopping malls, even certain retail and wholesale applications.

Features

- 15" Round Garage / Canopy Fixture
- Die Cast Aluminum Housing, Bronze Powder-coat Finish over a Chromate Conversion Coating
- Extended Clear Prismatic Polycarbonate Lens
- UL listed for wet locations
- IP43 Rated

Lamp & Ballast

A long lifetime rating of 100,000 hours or about 20 years operating hours 12 hours per 7 days per week. Electronic ballast features Class P rating, THD of less than 10%, constant output wattage, and fail-safe protection.

Warranty

Fixture guaranteed for 10 years against manufacturing defects.

Lamp and ballast guaranteed for 5 years.

Ordering Information	
G580	- 5K
Model	Color

MODEL	WATTS	*COLOR TEMP	VOLTS U = 120-277v	LUMENS	MAX LINE CURRENT AMP @ 120-277v	THD	DIMENSIONS (W x L)
G540	40w	5000k	U	3600lm	0.34 - 0.15	<10%	15" x 11.5"
G560	60w	5000k	U	5100lm	0.52 - 0.22	<10%	15" x 11.5"
G580	80w	5000k	U	6400lm	0.69 - 0.30	<10%	15" x 11.5"
G5100	100w	5000k	U	8000lm	0.87 - 0.37	<10%	15" x 11.5"
G5120	120w	5000k	U	9600lm	1.05 - 0.45	<10%	15" x 11.5"

(*Available Color Temp Range 3000k – 6500k (Warm to Cool) on request.)