

Ordering Information

# DIRECTLED BLE PL Plug-In Retrofit Lamp

#### FEATURES & SPECIFICATION SHEET

## Application

The BLE PL Series LED retrofit lamp, is specifically designed to replace HID, MH, and CFL lamps in existing light fixtures providing 60-90 percent in energy savings.

#### **Features**


- 360° beam angle, GX24d 2-pin or GX24q 4-pin Base
- Direct to AC (Direct Wire) connection or Ballast Compatible (Plug & Play)
- 120Lm/Watt LED Array
- Designed for use in open or enclosed fixtures
- Durable Aluminum Construction
- Compact Design
- IP64 Rated
- UL Listed

### **LED PCB & Driver**

A long lifecycle rating of 50,000 hours

# Warranty

Lamp is guaranteed for 5 years against manufacturing defects.



BLEPL7 - 5K - G24d							
Model Color Base							
MODEL	*COLOR TEMP	BASE d = 2 Pin q = 4 P	<b>DRIVER</b> U = 120 – 277V	WATTS	LUMENS	REPLACES (HPS MHL HID)	DIMENSIONS (E26/E39 & EX39 L x W)
BLEPL5	5000k	G24d / G24q	U	5w	600Lms	11w	4.8"x 1.77"
BLEPL7	5000k	G24d / G24q	U	7w	840Lms	13w	4.8"x 1.77"
BLEPL9	5000k	G24d / G24q	U	9w	1080Lms	18w	5.4"x 1.77"
BLEPL12	5000k	G24d / G24q	U	12w	1440Lms	26w	6.2"x 1.77"
BLEPL15	5000k	G24d / G24q	U	15w	1530Lms	32w	6.1"x 2.17"
BLEPL20	5000k	G24d / G24q	U	20w	2400Lms	42w	6.9"x 2.17"

(\*Available Color Temp Range 3000k – 6500k (Warm to Cool) on request.)

# EcoLightingUSA.com

Toll Free: (888) 326-9094 | Email: info@ecolightingusa.com | 217 Huyler Street, South Hackensack, NJ 07606