







DIRECTLED BLEIP Inverted Pyramid

Series

FEATURES & SPECIFICATION SHEET

Application

The BLEIP Inverted Pyramid Series LED Retrofit Lamp is specifically designed to replace High Pressure Sodium (HPS), Metal Halide (MHL), High Intensity Discharge (HID) and Compact Fluorescent (CFL) lamps in existing light fixtures providing 60-90% in energy savings.

Suitable for use in: High Bay, Area Lighting, Parking Lots, Street Lighting, Walkway Lighting, Post Top Lighting and much more.

Features

- 360° beam angle, E26 / E39 / EX39 Base
- Available in 120-277v or 300-480v (except 30w)
- Direct to AC (Direct Wire) connection
- High Efficiency 155 Lm/Watt LED Array
- Designed for use in open or enclosed fixtures
- Compact Design
- Flame Retardant
- UL Listed, Durable Construction

LED PCB & Driver

A long lifecycle rating of 50,000 hours

Warranty

Lamp is guaranteed for 5 years against manufacturing defects.















MODEL	*COLOR TEMP	BASE	VOLTS L = 120-277V H – 300-480V	WATTS	LUMENS	REPLACES (HPS MHL HID)	DIMENSIONS (E26/E39 L x W)	LISTED
BLEIP30	5000k	E26/E39/EX39	L	30w	4500Lms	100w	6.69"/7.09"x 5.2"	ETL
BLEIP40	5000k	E26/E39/EX39	L/H	40w	6000Lms	150w	6.69"/7.09"x 5.2"	ETL
BLEIP60	5000k	E26/E39/EX39	L/H	60w	9000Lms	200w	6.69"/7.09"x 5.2"	ETL

(*Available Color Temp Range 3000k – 6500k (Warm to Cool) on request.)