

Induction – IL5 SERIES

FEATURES & SPECIFICATION SHEET



Application

The IL5 series is an ideal choice for replacement of common Fluorescent and Metal Halide fixtures. Its electronic ballast features a high >0.98 power factor for cool, efficient, flicker free operation. Its electronic ballast features a high >0.98 power factor for cool, efficient, flicker free operation. Common applications include service corridors, offices, conference centers, interior stairwells, utility closets, lobbies, shopping malls, sports facilities, showrooms, supermarkets as well as a myriad of retail and wholes applications. IP20 rated.

Features

- Constructed of a stamped steel housing, Powder coat Finish over a Chromate Conversion Coating
- UV stabilized and heat resistant high transmission acrylic lens

Induction Lamp and Ballast

A long lifecycle rating of 100,000 hours or about 20 years operating hours 12 hours per 7 days per week. Induction Ballast features Class P rating, THD of less than 10, constant output wattage, and a fail-safe protection.

Warranty

All Induction Luminaires are guaranteed for 5 years against manufacturing defects. 10 Year Optional



100,000 HOURS

Ordering Information					
ECO-IL5-____-____-____-____ Example: (IL5-SB-40-27-UNV-W)					
MODEL	Lamp Type	Watts	CCT	Voltage	Lens Type
ECO-IL5	Inner Self Ballasted lamp	40	6500K	UNV 120vac-277vac	W=White G=Glossy
		60	5000K		
		80	4000K		
			3500K		
			3000K		
			2700K		