


DIRECTLED RD1 Induction Street Light

FEATURES & SPECIFICATION SHEET



Application

The RD1 series roadway fixture is an ideal choice for replacement of common HPS and Mercury Vapor cobra head fixtures. Its electronic ballast features a high >0.98 power factor for cool, efficient, flicker-free operation. Common applications include: general outdoor area lighting, boulevards, freeways, parkways, parking lots, and commercial security/flood applications. Type 3 distribution pattern with short cutoff.



Features

- 36" Round Garage / Canopy Fixture
- Tempered Flat Clear Glass Lens with aluminum reflector
- Die Cast Aluminum Housing & Hinged Top Frame, Powder coat Finish over a Chromate Conversion Coating
- UL 1598 listed for wet locations

Lamp & Ballast

A long lifetime rating of 100,000 hours or about 20 years operating hours 12 hours per 7 days per week. Electronic ballast features Class P rating, THD of less than 10%, constant output wattage, and fail-safe protection.

Warranty

Fixture guaranteed for 10 years against manufacturing defects. Lamp and ballast guaranteed for 5 years.

MODEL	WATTS	*COLOR TEMP	VOLTS U = 120-277v	DIMENSIONS (W x L)
RD140	40w	5000k	U	27" x 13"
RD160	60w	5000k	U	27" x 13"
RD180	80w	5000k	U	27" x 13"
RD1100	000w	5000k	U	27" x 13"