



Application

The G2 series aluminum garage fixture is an ideal choice for replacement of common High Pressure Sodium and Metal Halide Garage fixtures. Its electronic ballast features a high >0.98 power factor for cool, efficient, flicker-free operation. Common applications include: service hallways, parking garages, loading docks, stairwells, utility closets, gas stations, shopping malls, even certain retail and wholesale applications.

Features

- 12" Vandal Resistant Garage Fixture
- Die Cast Aluminum Housing with Bronze Powder-coat Finish
- Clear Prismatic Polycarbonate Lens
- UL 1598 listed for wet locations
- IP43 Rated

Lamp & Ballast

A long lifecycle rating of 100,000 hours or about 20 years operating 12 hours per day, 7 days per week.

Electronic ballast features THD of less than 10%, constant output wattage, and fail-safe protection.

Warranty

Fixture guaranteed for 10 years against manufacturing defects.

Lamp and ballast guaranteed for 5 years.

Ordering Information

G280 - 5K

Model Color

MODEL	WATTS	*COLOR TEMP	VOLTS U = 120-277v	DIMENSIONS (W x L)
G240	40w	5000k	U	12.38" x 8.38"
G260	60w	5000k	U	12.38" x 8.38"
G280	80w	5000k	U	12.38" x 8.38"
G2100	100w	5000k	U	12.38" x 8.38"

(*Available Color Temp Range 3000k – 6500k (Warm to Cool) on request.)